



The Public Health and Safety Organization

## NSF Product and Service Listings

These NSF Official Listings are current as of **Wednesday, March 02, 2022** at 12:15 a.m. Eastern Time. Please [contact NSF](#) to confirm the status of any Listing, report errors, or make suggestions.

Alert: NSF is concerned about fraudulent downloading and manipulation of website text. Always confirm this information by clicking on the below link for the most accurate information: <http://info.nsf.org/Certified/Plumbing/Listings.asp?Company=3C870&>

### MP Mechanical Plumbing Products

#### Goslyn LP

1904 University Business Drive  
Suite 310  
McKinney, TX 75071  
United States  
214-618-3764  
[Visit this company's website \(http://www.goslyn.com\)](http://www.goslyn.com)

**Facility :** Shanghai, China

Product Type	Material Type	Trade Product Name Standard
<i>Grease and Oil Separator# + ¢</i>	<i>MLTPL</i>	<i>GOS ASME 20 A112.14.4</i>

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

+ Flow Rate: 4 GPM.

¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.

<i>Grease and Oil Separator# * ¢</i>	<i>MLTPL</i>	<i>GOS ASME 8oLP A112.14.4</i>
--------------------------------------	--------------	------------------------------------

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

\* Flow Rate: 25 GPM.

¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.

<i>Grease and Oil Separator# * ¢</i>	<i>MLTPL</i>	<i>GOS ASME 8oLP A112.14.3</i>
--------------------------------------	--------------	------------------------------------

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

\* Flow Rate: 25 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

*Grease and Oil Separator# ¢ ++*

*MLTPL*

*GOS CSA  
60 B481.1*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

++ Flow Rate: 15 GPM.

*Grease and Oil Separator# % ¢*

*MLTPL*

*GOS CSA  
40 B481.1*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

% Flow Rate: 10 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

*Grease and Oil Separator# \* ¢*

*MLTPL*

*GOS CSA  
80 B481.1*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

\* Flow Rate: 25 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

*Grease and Oil Separator# + ¢*

*MLTPL*

*GOS ASME  
20 A112.14.3*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

+ Flow Rate: 4 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

*Grease and Oil Separator# \* ¢*

*MLTPL*

*GOS CSA  
80LP B481.1*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

\* Flow Rate: 25 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

*Grease and Oil Separator# + ¢**MLTPL**GOS CSA  
20 B481.1*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

+ Flow Rate: 4 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

*Grease and Oil Separator# ¢ ++**MLTPL**GOS ASME  
60 A112.14.3*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

++ Flow Rate: 15 GPM.

*Grease and Oil Separator# ¢ ++**MLTPL**GOS ASME  
60 A112.14.4*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

++ Flow Rate: 15 GPM.

*Grease and Oil Separator# % ¢ §**MLTPL**GOS ASME  
40 A112.14.3*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

% Flow Rate: 10 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the  
manufacturer's instructions and the requirements of the latest edition of the Uniform  
Plumbing Code™.

*Grease and Oil Separator# \* ¢ §**MLTPL**GOS ASME  
80 A112.14.3*

# Tested and rated as Type A: Units with an external flow control, with air intake (vent):  
directly connected.

\* Flow Rate: 25 GPM.

¢ Product is authorized to bear the CNSF and/or the CNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the  
manufacturer's instructions and the requirements of the latest edition of the Uniform  
Plumbing Code™.

*Grease and Oil Separator% ¢ §*

*MLTPL*

*GOS ASME*

*40 A112.14.4*

% Flow Rate: 10 GPM.

¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

*Grease and Oil Separator\* ¢ §*

*MLTPL*

*GOS ASME*

*80 A112.14.4*

\* Flow Rate: 25 GPM.

¢ Product is authorized to bear the cNSF and/or the cNSFus Mark.

§ Product is Certified to the Uniform Plumbing Code™. Installation in accordance with the manufacturer's instructions and the requirements of the latest edition of the Uniform Plumbing Code™.

---

Number of matching Manufacturers is 1

Number of matching Products is 15

Processing time was 1 seconds